


betonowy separator tłuszczów z osadnikiem,
przepustowość od 2 do 20 l/s



TYP	PRZEPUS- TOWOŚĆ NG l/s	POJ. OS. VO l	ŚR. ZEWN. ZB. DA mm	ŚR. WEWN. ZB. DI mm	ŚR. DOPŁYWU I ODPŁYWU DN mm	WYS. DO DNA RURY WLOT. HZ mm	WYS. DO DNA RURY WYLOT. HA mm	WYS. CAŁK. ZB. H mm	MASA NAJC. ELEM. G KG	MASA CAŁKO- WITA GG KG	NR KATALOG.
SF 2/200	2	200	1300	1000	150	1250	1180	1810	2150	2670	178021
SF 2/400	2	400	1300	1000	150	1450	1380	2010	2600	3120	178022
SF 4/400	4	400	1500	1200	150	1550	1480	2110	3300	4100	178042
SF 4/800	4	800	1800	1500	150	1250	1180	1810	3600	4900	178043
SF 7/700	7	700	1800	1500	150	1750	1680	2310	4560	5860	178073
SF 7/1400	7	1400	1800	1500	150	2150	2080	2710	5300	6600	178074
SF 10/1000	10	1000	2300	2000	150	1450	1380	2010	5550	7750	178104
SF 10/2000	10	2000	2300	2000	150	1750	1680	2310	6260	8460	178105
SF 20/2000	20	2000	2740	2500	200	1810	1740	2410	7040	10700	178205

Separatory betonowe są wyposażone standardowo we włazy w kl. D 400.